


DM2600 Series

Direct Mount Top Entry Flanged Ball Valve

DESIGN FEATURES

- Patented design - when valve is in "open" position, it's simple to take the bonnet out with the ball and seat at one time without using any tools
- Available in stainless steel or carbon steel
- Body and end are investment cast
- Blow-out proof stem design
- 100% air tested under water at 100 psi
- Working pressure ANSI 150
- Temperature range: -40°F to +450°F
- ISO 5211 mounting pad
- End cap type: flanged end (ANSI 150)
- Flange dimension: face-to-face ANSI B16.10; flange connection ANSI B16.50
- Silicone free
- Oxygen cleaned option
- Top entry ball valve is convenient for in-line repair
- Top entry ball valve simplifies the task of maintenance and decreases time spent on emergency repair



Size	Breakaway Torque (in-lb)	Cv	Weight lbs
1/2"	50	32	9
3/4"	75	54	10
1"	100	105	12
1-1/2"	185	275	18
2"	300	460	25
2-1/2"	450	780	36
3"	750	1330	50
4"	1100	2420	69
6"	3500	5400	189

ORDERING SCHEMATIC

Series	Material	Port	Packing	Seat	Ends
DM26	23 Carbon 33 Stainless 44 Alloy 20 77 Hastelloy C 99 Duplex	F Full R Reduced	C Carbon/Teflon G Graphite T Teflon	C Carbon T Teflon TM Super Teflon TC Carbon Super Teflon M Metal Seated	F1 Flanged 150 F3 Flanged 300



Right Valve, Right Application, Right Now!



Authorized Distributor

Quko Int'l Development Limited

Unit B, 17/F, EGL Tower, 83 Hung To Road, Kwun Tong, Kowloon, Hong Kong, China


Tel: (852) 2344 0201 Fax: (852) 2343 6078

Email: sales@qukointl.com

Website: www.qukointl.com


DIMENSIONS & MATERIAL SPECIFICATIONS

Item	Parts	Materials	
1	Body Flange	ASTM A351-CF8	ASTM A216-WCB
2	Bonnet	ASTM A351-CF8	ASTM A216-WCB
3	Ball	ASTM A351-CF8	ASTM A216-WCB
4	Stem	SS 316	
5	Ball Seats	PTFE/TFM	PTFE+25% Carbon
6	Thrust Washer	RPTFE	
7	Gasket	PTFE	Grafoil
8	O-Ring	Viton	
9	Stem Packing	PTFE	
10	Space Washer	SS 304	
11	Disc Washer	SS 301	
12	Stem Nut	SS 304	
13	Nut Stop	SS 304	
14	Stopper Plate	SS 304	
15	Handle	SS 304	
16	Handle Cover	Plastic	
17	Stop Pin	SS 304	
18	Bonnet Bolts	Grade B8	Grade B7
19	Lever Head	ASTM A351-CF8	
20	Set Bolt	SS 304	
21	Lever	Steel Pipe	



Size	d1	d2	d3	d4	d5	d6	d7	d8	H1	H2	H3	L1	L2	S
3/4"	0.77	0.77	0.28	0.24	1.97	1.65	M14	1.18	2.56	0.55	3.78	4.61	6.50	0.43
1"	0.77	1.00	0.28	0.24	1.97	1.65	M14	1.18	2.56	0.55	3.78	5.00	6.50	0.43
1-1/2"	1.26	1.50	0.36	0.28	2.76	1.97	M18	1.38	2.97	0.71	4.37	6.50	8.07	0.55
2"	1.50	2.00	0.36	0.28	2.76	1.97	M18	1.38	3.17	0.71	4.37	7.01	8.07	0.55
3"	2.25	3.07	0.45	0.36	4.02	2.76	M22	2.17	4.17	0.91	6.02	7.99	13.4	0.67
4"	2.99	4.00	0.45	0.36	4.02	2.76	M22	2.17	5.12	0.91	6.02	9.02	13.4	0.67

Size	Flange Dimensions (Class 150)					
	D	Bolt Hole				
		C	M	N	T	F
3/4"	3.86	2.76	0.63	0.16	0.45	0.06
1"	4.25	3.13	0.63	0.16	0.45	0.06
1-1/2"	5.00	3.88	0.63	0.16	0.56	0.06
2"	5.98	4.74	0.75	0.16	0.63	0.06
3"	7.48	6.00	0.75	0.16	0.75	0.06
4"	9.02	7.50	0.75	0.31	0.94	0.06



Right Valve, Right Application, Right Now!



Authorized Distributor
Quko Int'l Development Limited
 Unit B, 17/F, EGL Tower, 83 Hung To Road, Kwun Tong,
 Kowloon, Hong Kong, China
 Tel: (852) 2344 0201 Fax: (852) 2343 6078
 Email: sales@qukointl.com Website: www.qukointl.com