

Flow Switches

Series Y100 - Paddle type - Protection degree: Y102 IP55, Y105 IP65. SPDT contact 15 (8) A-230 V a.c.

MODEL	RANGE	OTHER FEATURES
Y106	1 to 85 m ³ /h	for liquids - 1" screwed connections for pipes Ø 1" to 8"
Y107	1 to 10 m ³ /s	for air - with paddle 175 x 80 mm



Pressure Switches

Series B300 - Metal bellows sensing element - 165 Ohm potentiometer - Die-cast aluminium case - IP55 protection.

MOD.	RANGE [kPa]	DIFFERENTIAL [kPa]	MAX SAFETY PRESSURE [kPa]	OTHER FEATURES
B301	10÷200	7÷30	600	copper alloy bellows
B302	100÷600	15÷120	900	
B303	200÷1400	60÷400	2200	
B304	500÷3000	80÷400	3800	
B301X	10÷200	7÷30	600	AISI 316 stainless steel bellows inox
B302X	100÷600	15÷120	900	
B303X	200÷1400	60÷400	2200	
B304X	500÷3000	80÷400	3800	
B353	200÷1400	150÷900	2200	
B353X	200÷1400	150÷900	2200	
B354	500÷3000	120÷900	3800	
B354X	500÷3000	12÷900	3800	



Level Controllers

Series FG650 - AISI 304 stainless steel float - Flanged connections - 165 Ohm potentiometer - Industrial water-proof case.

MODEL	MAX WORKING PRESSURE bar	PROPORTIONAL BAND mm	MAX WORKING TEMPERATURE °C	OTHER FEATURES
FG651	16	60	200	cast-iron body-connections 20 mm
FG653	30	60	230	cast-steel body-connections 20 mm



Level Controllers

Series FG600 - Float-type - AISI 304 stainless steel - Flanged connections - SPDT 10 (1) A-24 V a.c. - Industrial water-proof case - IP55 protection.

MODEL	MAX WORKING PRESSURE bar	DIFFERENTIAL mm	MAX WORKING TEMPERATURE °C	OTHER FEATURES
FG601	16	15 to 60	200	cast-iron body - connections 20 mm
FG603	30	25 to 60	230	stainless steel body connections 20 mm



Authorized Distributor
Quko Int'l Development Limited
 Unit B, 17/F, EGL Tower, 83 Hung To Road, Kwun Tong,
 Kowloon, Hong Kong, China
 Tel: (852) 2344 0201
 Email: sales@qukointl.com
 Fax: (852) 2343 6078
 Website: www.qukointl.com